

AIRSTAGE

FUJITSU

Multi Systems

Multiple Room Solutions



Why Choose Fujitsu?

Australia's Favourite Air®

Fujitsu General is a leading supplier of air conditioners in Australia, with a portfolio to suit both residential and commercial applications. We focus all of our research and manufacturing strengths into air conditioners which has resulted in our extensive range of world-class, energy efficient, market-leading air conditioners.

Fujitsu General strives to consistently provide high quality, reliable products accompanied by superior customer service. To be 'Australia's Favourite Air®' means to be the best air conditioning company to deal with in Australia, not just a leading air conditioning brand.

That's why we're proud to say we are 'Australia's Favourite Air®'.

Fujitsu Channel Partner Network

Fujitsu have a comprehensive network of dealers right across Australia. This ensures that there is a local stockist in your area to assist you in purchasing a Fujitsu air conditioning system for your home.

An Award Winning Brand

Fujitsu understands that our customers are investing in our brand and trusting that we will provide their family with a comfortable living environment all year round.

Fujitsu is honoured to be voted Reader's Digest Most Trusted Brand in the Air Conditioning category from 2018-2022 and awarded highly commended from 2023-2025.

Fujitsu General has also won the ProductReview.com.au Best Appliance Brands award for 2023-2025 and was recognised in the Finder Awards 2025 as both a Top Value and Most Loved Brand.



Peace of Mind

Fujitsu believe in the quality and reliability of every air conditioner we sell. This is why we're happy to provide a 5 year parts and labour warranty across the entire range.





✓
Exceptional after sales service

✓
Trusted brand

✓
5 year manufacturer's warranty

Sporting Chance

Fujitsu General Australia is extremely proud to be a major sponsor of the Sporting Chance Cancer Foundation. Established in 1996, Sporting Chance is a not-for-profit organisation that helps provide home support and care to children with cancer.



To date, Fujitsu General has donated more than \$11M to this worthy cause, with a percentage of sales from Fujitsu's air conditioning units going towards the funding of outreach programs and exploring better ways to treat and overcome cancer. Sporting Chance initiatives allow families to spend more quality time at home together, while still having access to the appropriate care for their child.

State of the Art Research and Development

Our state of the art research and development centre, located at our headquarters in Japan, is equipped with numerous testing facilities simulating a variety of air conditioning operating conditions. Our rigorous testing aims to meet Fujitsu's high standard of product quality and reliability.

Exceptional After Sales Service

At Fujitsu, we pride ourselves on providing exceptional customer service. Fujitsu General Assist is our in-house customer care and technical support department which was implemented to deliver a high level of support and accessibility to our customers.

Fujitsu General Assist deploys Fujitsu-trained technicians in Sydney, Melbourne, Brisbane, Adelaide, and Perth and provides access to dedicated Service Agents in all other parts of Australia. These technicians are well equipped with the necessary tools and spare parts to enable them to resolve issues onsite, promptly. This offers customers a high first time fix rate and seamless experience.





Multi Systems

A variety of indoor models ranging in capacity class from 2.0kW to 7.0kW




What are Multi Systems?

A multi system is ideal when individual units are required in more than one room and when a traditional whole home ducted system may not be suitable due to the home's design.

A multi system can cool or heat multiple rooms, allowing for a variety of up to five indoor units to be connected to just one compact outdoor unit. This means greater installation flexibility and outdoor space saving options.

Wide Range of Options

Fujitsu General's entire range of multi systems now feature R32 refrigerant. The use of R32 refrigerant improves heat transfer and compared to the commonly used R410A refrigerant, has a 67 per cent¹ lower 'Global Warming Potential Factor' whilst still maintaining the performance of the unit. The 3 room outdoor unit has a rated cooling capacity of 6.8kW, the 4 room outdoor unit has a rated cooling capacity of 8.0kW and the 5 room outdoor units have rated cooling capacities of 10.0kW and 12.5kW.



Extensive indoor unit line-up

The range of connectable indoor units on the 3 and 4 room multi systems have been extended to 22 models across 7 different styles, including wall mounted, bulkhead, slimline, mini duct, cassette, ceiling console, and floor mounted. The connectable indoor units on the 5 room multi systems have also been extended to 19 models across 6 different styles, including wall mounted, bulkhead, slimline, mini duct, compact cassette and ceiling console. This flexibility ensures a tailored solution for each room. The indoor units can be controlled individually via a remote control or simultaneously via an optional central controller.

Flexible Installation


Due to the latest design, flexible installation of the outdoor unit is possible even in limited and narrow spaces.

R32 Multi Systems

- ✓ Up to 22 indoor units to choose from
- ✓ Space saving - requires only one outdoor unit
- ✓ Individual room temperature control
- ✓ R32 refrigerant
- ✓ Central controller option
- ✓ Easy installation and setup


Indoor units	Range	Models
	BULKHEAD Capacity Class from 2.5kW to 5.0kW	ARTH09KLLAP ARTH12KLLAP ARTH18KLLAP
	MINI DUCT Capacity Class from 2.5kW to 5.0kW	ARTH09KSLAP ARTH12KSLAP ARTH18KSLAP
	MID STATIC SLIMLINE Capacity Class from 5.0kW to 7.0kW	ARTH18KMTAP ARTH24KMTAP
	WALL MOUNTED Capacity Class from 2.0kW to 7.0kW	ASTH07KMCD ASTH14KMCD ASTH24KMTE ASTH09KMCD ASTH18KMTD ASTH12KMCD ASTH22KMTD
	CASSETTE Capacity Class from 2.5kW to 5.0kW	AUTH09KVLA-GR AUTH12KVLA-GR AUTH18KVLA-GR
	FLOOR MOUNT Capacity Class from 2.5kW to 4.0kW	AGTG09KVCA AGTG12KVCA AGTG14KVCA
Not compatible with 5 room multi outdoor units AOTH36KBTA5 and AOTH45KBTA5.		
	CEILING CONSOLE Capacity Class of 5.0kW	ABTH18KRTA

3 Room set-up



AOTH24KBCA3

4 Room set-up



AOTH30KBT4

5 Room set-up



AOTH36KBT5
AOTH45KBT5

Feature Checklist

		ARTH09KLLAP	ARTH12KLLAP	ARTH18KLLAP	ARTH09KSLAP	ARTH12KSLAP	ARTH18KSLAP	ARTH18KMTAP	ARTH24KMTAP
		BULKHEAD			MINI DUCT			MID STATIC SLIMLINE	
10°C Heat Operation	The room temperature can be set to go no lower than 10°C, ensuring that the room does not get too cold when not occupied								
Apple-Catechin Filter	Fine dust, invisible mould spores and harmful microorganisms are absorbed onto the filter by static electricity and further growth is inhibited and deactivated by the polyphenol ingredient extracted from apples								
Auto Changeover	Automatically switches between operating modes based on the temperature setting and room temperature	✓	✓	✓	✓	✓	✓	✓	✓
Auto Restart	The unit will automatically restart in the same operating mode after a temporary loss of power	✓	✓	✓	✓	✓	✓	✓	✓
Automatic Fan Speed	The micro processor automatically adjusts the airflow effectively to follow the changes of room temperature	✓	✓	✓	✓	✓	✓	✓	✓
Automatic Louvre	The position of the louvres is set automatically to match the operating mode. It is also possible to adjust the louvres using the remote control								
Connectable Distributing Duct	Systems are capable of attaching field-supplied branch ducts distributing the airflow							✓	✓
Connectable Fresh Air Duct	Systems are capable of attaching field-supplied branch ducts to bring fresh air in							✓	✓
Economy Mode	The temperature will adjust by 1°C to allow for a reduction in power drawn from the compressor to help save energy	✓	✓	✓	✓	✓	✓	✓	✓
Filter Sign	Set the interval frequency to be reminded to clean the air filter on your unit							✓	✓
Human Sensor	The human sensor detects movement so that when occupants leave the room, the heat pump/air conditioner switches into energy saving mode after 20 minutes should no movement be detected. When occupants re-enter the room, it returns to normal operation								
Long-life Ion Deodorisation Filter	The filter deodorises by powerfully decomposing absorbed odours using the oxidising and reducing effects of ion generated by the ultra-fine-particle ceramic								
Low Noise Mode	The compressor speed and the outdoor unit fan speed are limited to reduce the operational noise								
On-Off Timer	Can be set to operate once every 24 hours	✓	✓	✓	✓	✓	✓	✓	✓
Program Timer	Allows selection of one of four options. ON, OFF, ON→OFF, or OFF→ON	✓	✓	✓	✓	✓	✓	✓	✓
Powerful Mode	This mode will operate the heat pump/air conditioner at maximum capacity for 20 minutes, providing comfort faster than ever before								
Sleep Timer	The micro-processor gradually changes the room temperature, allowing you to sleep comfortably at night	✓	✓	✓	✓	✓	✓	✓	✓
Super Quiet Mode	The indoor units fan can operate at a low speed to produce quieter operation								
Washable Panel	Dust which accumulates on the heat pump/air conditioner can be easily cleaned with a damp cloth.								
Weekly Timer	Different on-off timers can be set for up to 7 days	✓	✓	✓	✓	✓	✓	✓	✓

ASTH07KMCD	ASTH09KMCD	ASTH12KMCD	ASTH14KMCD	ASTH18KMTD	ASTH22KMTD	ASTH24KMTE	AUTH09K/LA-GR	AUTH12K/LA-GR	AUTH18K/LA-GR	AGTG09K/CA*	AGTG12K/CA*	AGTG14K/CA*	ABTH18KRTA
WALL MOUNTED							CASSETTE			FLOOR MOUNT			CEILING CONSOLE
✓	✓	✓	✓	✓	✓	✓				✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓				✓	✓	✓	
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				
✓	✓	✓	✓	✓	✓	✓							
✓	✓	✓	✓	✓	✓	✓				✓	✓	✓	
✓	✓	✓	✓	✓	✓	✓				✓	✓	✓	
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓							
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	■
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓				✓	✓	✓	□

*Not compatible with 5 room multi outdoor units AOTH36KBTA5 and AOTH45KBTA5.

■ Available when using a wireless remote only.


□ Only available when using a UTY-RNRYT5.

Multi System Controller Options

Wired remote controller



UTY-RVRY



UTY-RNRYT5
UTY-RNRYZ3



UTY-RVNYN

Wireless remote controller



AR-REJ1E



AR-REW3E



AR-REW1E



AR-REM7E

Central controller



UTY-DMMYM1

IR receiver unit



UTY-LBTYM

OR



UTY-LBTYH

+



Simple remote controller



UTY-RSRYT



UTY-RHRYT




UTY-RSNYN

TYPE	MODEL	WALL MOUNTED		FLOOR	CEILING CONSOLE	COMPACT CASSETTE	BULKHEAD / MINI DUCT	MID STATIC SLIMLINE
		KMCD	18KMTD / 24KMTE	KVCA*	KRTA	KVLA	KSLAP / KLLAP	KMTAP
WIRED REMOTE CONTROLLER	UTY-RNRYZ3	-	-	-	-	-	A	-
	UTY-RNRYT5	○ ¹	○ ¹	○ ²	○	○	○	○
	UTY-RNRT	-	-	-	-	-	-	A
	UTY-RVNYN	-	-	-	-	-	-	○
	UTY-RVRY	○	○	○	○	○	○	○
GROUP CONTROLLER	UTY-DMMYM1	○ ¹	○ ¹	○ ²	○	○	○	○
WIRELESS REMOTE CONTROLLER	AR-REJ1E	-	-	-	-	A	-	-
	AR-REW3E	A	-	-	-	-	-	-
	AR-REW1E	-	A	-	-	-	-	-
	AR-REM7E	-	-	A	-	-	-	-
IR RECEIVER UNIT	UTY-LBTYM	-	-	-	-	○	○	○
	UTY-LBTYH	-	-	-	○	-	-	-
SIMPLE REMOTE CONTROLLER	UTY-RSRYT	○ ¹	○ ¹	○ ²	○	○	○	○
	UTY-RHRYT	○ ¹	○ ¹	○ ²	○	○	○	○
	UTY-RSNYN	-	-	-	-	-	-	○

A Standard Accessory ○ Optional ○¹ Optional Communication Kit (UTY-TWRXZ2) is necessary for the installation.

○² Optional Communication Kit (UTY-TWRXZ3) is necessary for the installation.

*Not compatible with 5 room multi outdoor units AOTH36KBTA5 and AOTH45KBTA5.



R32 Product Specifications

Wall Mounted - Lifestyle (Small)

MODEL NUMBER				ASTH07KMCD	ASTH09KMCD
kW Class		kW		2.0kW Class	2.5kW Class
Power Source		V/PH/HZ		220-240 / 1 / 50	
Noise Level	Cool	H / M / L / Q	dBA	38 / 34 / 29 / 21	40 / 35 / 30 / 21
	Heat			41 / 36 / 31 / 22	42 / 36 / 31 / 22
Air Circulation	Cool	H / M / L / Q	l/sec	181 / 150 / 119 / 75	194 / 156 / 119 / 75
	Heat			200 / 161 / 128 / 92	208 / 169 / 131 / 92
Net Dimensions		H x W x D	mm	270 x 834 x 222	270 x 834 x 222
Net Weight		kg		10	10
Pipe Size	Liquid / Gas		mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52



Wall Mounted - Lifestyle (Small - Medium)

MODEL NUMBER				ASTH12KMCD	ASTH14KMCD
kW Class		kW		3.5kW Class	4.0kW Class
Power Source		V/PH/HZ		220-240 / 1 / 50	
Noise Level	Cool	H / M / L / Q	dBA	40 / 35 / 30 / 21	43 / 36 / 30 / 21
	Heat			42 / 38 / 33 / 22	44 / 39 / 33 / 24
Air Circulation	Cool	H / M / L / Q	l/sec	194 / 156 / 119 / 75	214 / 167 / 125 / 78
	Heat			214 / 178 / 144 / 92	222 / 183 / 144 / 94
Net Dimensions		H x W x D	mm	270 x 834 x 222	270 x 834 x 222
Net Weight		kg		10	10
Pipe Size	Liquid / Gas		mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52



Wall Mounted - Lifestyle (Medium - Large)

MODEL NUMBER				ASTH18KMTD	ASTH22KMTD	ASTH24KMTE
kW Class		kW		5.0kW Class	6.0kW Class	7.0kW Class
Power Source		V/PH/HZ		220-240 / 1 / 50		
Noise Level	Cool	H / M / L / Q	dBA	45 / 40 / 35 / 29	48 / 40 / 35 / 29	49 / 40 / 35 / 29
	Heat			46 / 40 / 35 / 29	48 / 40 / 35 / 29	49 / 40 / 35 / 29
Air Circulation	Cool	H / M / L / Q	l/sec	272 / 225 / 178 / 142	294 / 225 / 178 / 142	325 / 236 / 178 / 142
	Heat			283 / 236 / 178 / 142	294 / 236 / 178 / 142	325 / 236 / 178 / 142
Net Dimensions		H x W x D	mm	280 x 980 x 240	280 x 980 x 240	280 x 980 x 240
Net Weight		kg		12.5	12.5	12.5
Pipe Size	Liquid / Gas		mm	Ø6.35 / Ø12.70	Ø6.35 / Ø12.70	Ø6.35 / Ø12.70



Floor Mount

MODEL NUMBER				AGTG09KVCA*	AGTG12KVCA*	AGTG14KVCA*
kW Class		kW		2.5kW Class	3.5kW Class	4.0kW Class
Power Source		V/PH/HZ		220-240 / 1 / 50		
Noise Level	Cool	H / M / L / Q	dBA	39 / 34 / 28 / 22	42 / 36 / 30 / 22	44 / 38 / 31 / 22
	Heat			39 / 35 / 30 / 22	42 / 38 / 32 / 22	44 / 39 / 33 / 22
Air Circulation	Cool	H / M / L / Q	l/sec	147 / 122 / 100 / 75	167 / 136 / 106 / 75	181 / 144 / 111 / 75
	Heat			147 / 128 / 106 / 75	167 / 142 / 114 / 75	181 / 150 / 119 / 75
Net Dimensions		H x W x D	mm	600 x 740 x 200	600 x 740 x 200	600 x 740 x 200
Net Weight		kg		14.00	14.00	14.00
Pipe Size	Liquid / Gas		mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52

*Not compatible with 5 room multi outdoor units AOTH36KBTAS and AOTH45KBTAS.



Ceiling Console

MODEL NUMBER				ABTH18KRTA
kW Class		kW		5.0kW Class
Power Source		V/PH/HZ		220-240 / 1 / 50
Noise Level	Cool	H / M / L / Q	dBA	38 / 36 / 33 / 31
	Heat			38 / 36 / 33 / 31
Air Circulation	Cool	H / M / L / Q	l/sec	233 / 219 / 197 / 181
	Heat			233 / 219 / 197 / 181
Net Dimensions		H x W x D	mm	235 x 1080 x 705
Net Weight		kg		24.00
Pipe Size	Liquid / Gas		mm	Ø6.35 / Ø12.70




Cassette

MODEL NUMBER				AUTH09KVL-GR	AUTH12KVL-GR	AUTH18KVL-GR
kW Class			kW	2.5kW Class	3.5kW Class	5.0kW Class
Power Source			V/PH/Hz	220-240 / 1 / 50		
Noise Level	Cool	H / M / L / Q	dBA	33 / 31 / 29 / 27	37 / 34 / 31 / 28	42 / 37 / 33 / 29
	Heat			34 / 32 / 29 / 27	37 / 34 / 31 / 29	44 / 41 / 37 / 30
Air Circulation	Cool	H / M / L / Q	l/sec	150 / 136 / 122 / 108	169 / 147 / 131 / 114	208 / 169 / 144 / 114
	Heat			150 / 136 / 122 / 108	169 / 147 / 131 / 114	222 / 197 / 167 / 125
Grille Model Number				UTG-UFYF-W	UTG-UFYF-W	UTG-UFYF-W
Net Dimensions - Indoor		H x W x D	mm	245 x 570 x 570	245 x 570 x 570	245 x 570 x 570
Net Weight - Indoor			kg	15	15	15
Net Dimensions - Grille		H x W x D	mm	49 x 620 x 620	49 x 620 x 620	49 x 620 x 620
Weight - Grille			kg	2.30	2.30	2.30
Pipe Size	Liquid / Gas		mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø12.7



Compact Bulkhead

MODEL NUMBER				ARTH09KLLAP	ARTH12KLLAP	ARTH18KLLAP	
kW Class				kW	2.5kW Class	3.5kW Class	5.0kW Class
Power Source				V/PH/HZ	220-240 / 1 / 50		
Noise Level	Cool	H / M / L / Q	dBA	28 / 27 / 26 / 24	29 / 28 / 27 / 26	32 / 30 / 29 / 27	
	Heat			28 / 26 / 25 / 24	29 / 28 / 27 / 24	32 / 30 / 29 / 27	
Air Circulation	Cool	H / M / L / Q	l/sec	167 / 153 / 139 / 125	181 / 167 / 153 / 133	261 / 244 / 228 / 208	
	Heat			167 / 153 / 139 / 125	181 / 167 / 153 / 133	261 / 244 / 228 / 208	
Static Pressure Range				Pa	0-90	0-90	0-90
Net Dimensions			H x W x D	mm	198 x 700 x 620	198 x 700 x 620	198 x 900 x 620
Net Weight				kg	17.00	17.00	20.00
Pipe Size	Liquid / Gas			mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø12.7




Mini Duct

MODEL NUMBER				ARTH09KSLAP	ARTH12KSLAP	ARTH18KSLAP	
kW Class				kW	2.5kW Class	3.5kW Class	5.0kW Class
Power Source				V/PH/HZ	220-240 / 1 / 50		
Noise Level	Cool	H / M / L / Q	dBA	29 / 26 / 24 / 23	31 / 27 / 25 / 23	33 / 29 / 26 / 23	
	Heat			29 / 26 / 24 / 23	31 / 27 / 25 / 23	33 / 29 / 26 / 23	
Air Circulation	Cool	H / M / L / Q	l/sec	167 / 125 / 111 / 100	181 / 136 / 119 / 100	261 / 208 / 150 / 133	
	Heat			167 / 125 / 111 / 100	181 / 136 / 119 / 100	261 / 208 / 150 / 133	
Static Pressure Range				Pa	0-30	0-30	0-50
Net Dimensions			H x W x D	mm	198 x 700 x 450	198 x 700 x 450	198 x 900 x 450
Net Weight				kg	15.50	15.50	18.50
Pipe Size	Liquid / Gas			mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø12.7



Mid Static Slimline

MODEL NUMBER				ARTH18KMTAP	ARTH24KMTAP
kW Class			kW	5.0kW Class	7.0kW Class
Power Source			V/PH/HZ	220-240 / 1 / 50	
Noise Level	Cool	H / M / L / Q	dBA	33 / 28 / 25 / 23	38 / 33 / 30 / 27
	Heat			33 / 28 / 25 / 23	38 / 33 / 30 / 27
Air Circulation	Cool	H / M / L / Q	l/sec	300 / 239 / 211 / 181	417 / 325 / 283 / 239
	Heat			300 / 239 / 211 / 181	417 / 325 / 283 / 239
Static Pressure Range			Pa	50 - 150	50-150
Net Dimensions		H x W x D	mm	240 x 1000 x 700	240 x 1000 x 700
Net Weight			kg	31.00	31.00
Pipe Size	Liquid / Gas		mm	Ø6.35 / Ø12.7	Ø6.35 / Ø12.7



Outdoor Product Specifications

Outdoor Unit			AOTH24KBCA3	AOTH30KBTA4	AOTH36KBTA5	AOTH45KBTA5	
Power Source	V / Ph / Hz		220-240 / 1/ 50				
Capacity	Cooling (Rated (Min - Max))	kW	6.8 (1.8 - 8.5)	8.0 (2.4 - 10.1)	10.0 (3.5 - 12.5)	12.5 (3.5 - 14.0)	
	Heating (Rated (Min - Max))	kW	8.0 (2.0 - 9.2)	9.6 (3.0 - 12.0)	12.0 (3.5 - 14.0)	13.5 (3.5 - 16.0)	
Input Power	Cooling (Rated (Max))	kW	1.74 (2.65)	2.05 (2.88)	2.44 (3.70)	3.57 (4.20)	
	Heating (Rated (Max))	kW	1.76 (2.35)	2.00 (3.25)	2.47 (3.10)	2.93 (4.00)	
EER	Cooling	kW / kW	3.90	3.90	4.10	3.50	
COP	Heating	kW / kW	4.54	4.80	4.86	4.50	
TCSPF ¹	Residential (Hot/Average/Cold)	kW	5.601 / 5.332 / 5.642	5.663 / 5.402 / 5.72	5.744 / 5.477 / 5.763	5.537 / 5.277 / 5.696	
HSPF ²	Residential (Hot/Average/Cold)	kW	5.583 / 4.919 / 4.161	5.548 / 4.951 / 4.183	5.799 / 5.148 / 4.351	5.755 / 5.041 / 4.300	
Running current	Cooling/Heating		amps	7.7 / 7.8	9.1 / 8.9	10.8 / 11.0	15.8 / 13.0
Sound Pressure Level ³	Outdoor (Cooling/Heating)	High	dBA	46 / 52	48 / 54	52 / 54	53 / 55
Sound Power Level	Outdoor	High		61	65	68	69
Dimensions	Outdoor	H x W x D	mm	716 x 820 x 315	884 x 820 x 315	998 x 940 x 320	998 x 940 x 320
Net Weight	Outdoor		kg	46	59	74	74
Connection Pipe Sizes	Unit A	Liquid / Gas	mm	6.35 / 12.7	6.35 / 12.7	6.35 / 12.7	6.35 / 12.7
	Unit B			6.35 / 9.52	6.35 / 12.7	6.35 / 12.7	6.35 / 12.7
	Unit C			6.35 / 9.52	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
	Unit D			-	6.35 / 9.52	6.35 / 9.52	6.35 / 9.52
	Unit E			-	-	6.35 / 9.52	6.35 / 9.52
Pipe Length (Max (Precharged))		m	50 (30)	70 (40)	80 (50)	80 (50)	
Max Height Difference		m	15	15	15	15	
Max Heigh Difference (between indoor units)		m	10	10	10	10	
Operation Range	Outdoor (Min - Max)	Cooling	°CDB	-10 to 50	-10 to 50	-15 to 50	-15 to 50
		Heating		-15 to 24	-15 to 24	-15 to 24	-15 to 24
Refrigerant	Type		R32	R32	R32	R32	
	Charge	g	1800	2500	3000	3000	

¹ Total Cooling Seasonal Performance Factor

² Heating Seasonal Performance Factor

³ Measured values in manufacturer's anechoic chamber. Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

Specifications and features

Products in this brochure contain R32 refrigerant. Please refer to specifications before installation and servicing this product. Only persons and / or companies qualified and experienced in the installation, service and repair of refrigerant products should be permitted to do so. The purchaser must ensure that the person and / or company who is to install, service or repair this air conditioner has qualifications and experience in refrigerant products. Suitable access for warranty and service is required. Future improvements, specifications, designs of product and availability are subject to change without notice. Please check with your Dealer.

All Capacity and Energy Efficiency ratings are based on AS / NZS3823.2.

Cooling Indoor temperature 27°C DB / 19°C WB
Outdoor temperature 35°C DB

Heating Indoor temperature 20°C DB
Outdoor temperature 7°C DB / 6°C WB

Running current is at rated conditions (AS3823) and does not include compressor start-up or variations in power supply and load conditions.



Connection Charts

AOTH24KBCA3 (2 - 3 ROOMS)

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	TOTAL
1	7	7	-	14
2	7	9	-	16
3	7	12	-	19
4	7	14	-	21
5	7	18	-	25
6	9	9	-	18
7	9	12	-	21
8	9	14	-	23
9	9	18	-	27
10	12	12	-	24
11	12	14	-	26
12	12	18	-	30
13	14	14	-	28
14	14	18	-	32
15	7	7	7	21
16	7	7	9	23
17	7	7	12	26
18	7	7	14	28
19	7	7	18*	32
20	7	9	9	25
21	7	9	12	28
22	7	9	14	30
23	7	9	18*	34
24	7	12	12	31
25	7	12	14	33
26	7	14	14	35
27	9	9	9	27
28	9	9	12	30
29	9	9	14	32
30	9	9	18*	36
31	9	12	12	33
32	9	12	14	35
33	12	12	12	36

AOTH30KBT4 (2 - 4 ROOMS)

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	TOTAL
1	7	22	-	-	29
2	7	24	-	-	31
3	9	22	-	-	31
4	9	24	-	-	33
5	12	22	-	-	34
6	12	24	-	-	36
7	14	18	-	-	32
8	14	22	-	-	36
9	14	24	-	-	38
10	18	18	-	-	36
11	18	22	-	-	40
12	18	24	-	-	42
13	22	22	-	-	44
14	22	24	-	-	46
15	24	24	-	-	48
16	7	7	12	-	26
17	7	7	14	-	28
18	7	7	18	-	32
19	7	7	22	-	36
20	7	7	24	-	38
21	7	9	9	-	25
22	7	9	12	-	28
23	7	9	14	-	30
24	7	9	18	-	34
25	7	9	22	-	38
26	7	9	24	-	40
27	7	12	12	-	31
28	7	12	14	-	33
29	7	12	18	-	37
30	7	12	22	-	41
31	7	12	24	-	43
32	7	14	14	-	35
33	7	14	18	-	39
34	7	14	22	-	43
35	7	14	24	-	45
36	7	18	18	-	43
37	7	18	22	-	47
38	7	18	24	-	49
39	9	9	9	-	27
40	9	9	12	-	30
41	9	9	14	-	32
42	9	9	18	-	36
43	9	9	22	-	40
44	9	9	24	-	42
45	9	12	12	-	33
46	9	12	14	-	35
47	9	12	18	-	39
48	9	12	22	-	43
49	9	12	24	-	45
50	9	14	14	-	37
51	9	14	18	-	41
52	9	14	22	-	45
53	9	14	24	-	47
54	9	18	18	-	45
55	9	18	22	-	49
56	12	12	12	-	36
57	12	12	14	-	38

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	TOTAL
58	12	12	18	-	42
59	12	12	22	-	46
60	12	12	24	-	48
61	12	14	14	-	40
62	12	14	18	-	44
63	12	14	22	-	48
64	12	18	18	-	48
65	14	14	14	-	42
66	14	14	18	-	46
67	7	7	7	7	28
68	7	7	7	9	30
69	7	7	7	12	33
70	7	7	7	14	35
71	7	7	7	18	39
72	7	7	7	22	43
73	7	7	7	24	45
74	7	7	9	9	32
75	7	7	9	12	35
76	7	7	9	14	37
77	7	7	9	18	41
78	7	7	9	22	45
79	7	7	9	24	47
80	7	7	12	12	38
81	7	7	12	14	40
82	7	7	12	18	44
83	7	7	12	22	48
84	7	7	14	14	42
85	7	7	14	18	46
86	7	9	9	9	34
87	7	9	9	12	37
88	7	9	9	14	39
89	7	9	9	18	43
90	7	9	9	22	47
91	7	9	9	24	49
92	7	9	12	12	40
93	7	9	12	14	42
94	7	9	12	18	46
95	7	9	14	14	44
96	7	9	14	18	48
97	7	12	12	12	43
98	7	12	12	14	45
99	7	12	12	18	49
100	7	12	14	14	47
101	7	14	14	14	49
102	9	9	9	9	36
103	9	9	9	12	39
104	9	9	9	14	41
105	9	9	9	18	45
106	9	9	9	22	49
107	9	9	12	12	42
108	9	9	12	14	44
109	9	9	12	18	48
110	9	9	14	14	46
111	9	12	12	12	45
112	9	12	12	14	47
113	9	12	14	14	49
114	12	12	12	12	48

2 - 4 Room Multi System Unit Reference Guide

UNIT NO.	BULKHEAD	MINI DUCT	MID STATIC SLIMLINE	WALL MOUNTED	CASSETTE	FLOOR MOUNT	CEILING CONSOLE
7				ASTH07KMCD			
9	ARTH09KLLAP	ARTH09KSLAP		ASTH09KMCD	AUTH09KVL-GR	AGTG09KVCA	
12	ARTH12KLLAP	ARTH12KSLAP		ASTH12KMCD	AUTH12KVL-GR	AGTG12KVCA	
14				ASTH14KMCD		AGTG14KVCA	
18	ARTH18KLLAP	ARTH18KSLAP	ARTH18KMTAP	ASTH18KMTD	AUTH18KVL-GR		ABTH18KRTA
22				ASTH22KMTD			
24			ARTH24KMTAP	ASTH24KMTE			

NOTE: The connection charts reference possible combinations as per capacity class, please refer to technical manual for actual indoor capacities.
*Mid Static Slimline cannot be connected in this combination.

A0TH36KBTA5 (2 - 5 ROOMS)

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
1	7	24	-	-	-	31
2	9	22	-	-	-	31
3	9	24	-	-	-	33
4	12	22	-	-	-	34
5	12	24	-	-	-	36
6	14	22	-	-	-	36
7	14	24	-	-	-	38
8	18	18	-	-	-	36
9	18	22	-	-	-	40
10	18	24	-	-	-	42
11	22	22	-	-	-	44
12	22	24	-	-	-	46
13	24	24	-	-	-	48
14	7	7	14	-	-	28
15	7	7	18	-	-	32
16	7	7	22	-	-	36
17	7	7	24	-	-	38
18	7	9	12	-	-	28
19	7	9	14	-	-	30
20	7	9	18	-	-	34
21	7	9	22	-	-	38
22	7	9	24	-	-	40
23	7	12	12	-	-	31
24	7	12	14	-	-	33
25	7	12	18	-	-	37
26	7	12	22	-	-	41
27	7	12	24	-	-	43
28	7	14	14	-	-	35
29	7	14	18	-	-	39
30	7	14	22	-	-	43
31	7	14	24	-	-	45
32	7	18	18	-	-	43
33	7	18	22	-	-	47
34	7	18	24	-	-	49
35	9	9	9	-	-	27
36	9	9	12	-	-	30
37	9	9	14	-	-	32
38	9	9	18	-	-	36
39	9	9	22	-	-	40
40	9	9	24	-	-	42
41	9	12	12	-	-	33
42	9	12	14	-	-	35
43	9	12	18	-	-	39
44	9	12	22	-	-	43
45	9	12	24	-	-	45
46	9	14	14	-	-	37
47	9	14	18	-	-	41
48	9	14	22	-	-	45
49	9	14	24	-	-	47
50	9	18	18	-	-	45
51	9	18	22	-	-	49
52	9	18	24	-	-	51
53	12	12	12	-	-	36
54	12	12	14	-	-	38
55	12	12	18	-	-	42
56	12	12	22	-	-	46
57	12	12	24	-	-	48
58	12	14	14	-	-	40
59	12	14	18	-	-	44
60	12	14	22	-	-	48
61	12	14	24	-	-	50
62	12	18	18	-	-	48
63	12	18	22	-	-	52
64	12	18	24	-	-	54
65	14	14	14	-	-	42

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
66	14	14	18	-	-	46
67	14	14	22	-	-	50
68	14	14	24	-	-	52
69	14	18	18	-	-	50
70	18	18	18	-	-	54
71	7	7	7	7	-	28
72	7	7	7	9	-	30
73	7	7	7	12	-	33
74	7	7	7	14	-	35
75	7	7	7	18	-	39
76	7	7	7	22	-	43
77	7	7	7	24	-	45
78	7	7	9	9	-	32
79	7	7	9	12	-	35
80	7	7	9	14	-	37
81	7	7	9	18	-	41
82	7	7	9	22	-	45
83	7	7	9	24	-	47
84	7	7	12	12	-	38
85	7	7	12	14	-	40
86	7	7	12	18	-	44
87	7	7	12	22	-	48
88	7	7	12	24	-	50
89	7	7	14	14	-	42
90	7	7	14	18	-	46
91	7	7	14	22	-	50
92	7	7	14	24	-	52
93	7	7	18	18	-	50
94	7	9	9	9	-	34
95	7	9	9	12	-	37
96	7	9	9	14	-	39
97	7	9	9	18	-	43
98	7	9	9	22	-	47
99	7	9	9	24	-	49
100	7	9	12	12	-	40
101	7	9	12	14	-	42
102	7	9	12	18	-	46
103	7	9	12	22	-	50
104	7	9	12	24	-	52
105	7	9	14	14	-	44
106	7	9	14	18	-	48
107	7	9	14	22	-	52
108	7	9	14	24	-	54
109	7	9	18	18	-	52
110	7	12	12	12	-	43
111	7	12	12	14	-	45
112	7	12	12	18	-	49
113	7	12	14	14	-	47
114	7	12	14	18	-	51
115	7	14	14	14	-	49
116	7	14	14	18	-	53
117	9	9	9	9	-	36
118	9	9	9	12	-	39
119	9	9	9	14	-	41
120	9	9	9	18	-	45
121	9	9	9	22	-	49
122	9	9	9	24	-	51
123	9	9	12	12	-	42
124	9	9	12	14	-	44
125	9	9	12	18	-	48
126	9	9	12	22	-	52
127	9	9	12	24	-	54
128	9	9	14	14	-	46
129	9	9	14	18	-	50
130	9	9	18	18	-	54

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
131	9	12	12	12	-	45
132	9	12	12	14	-	47
133	9	12	12	18	-	51
134	9	12	14	14	-	49
135	9	12	14	18	-	53
136	9	14	14	14	-	51
137	12	12	12	12	-	48
138	12	12	12	14	-	50
139	12	12	12	18	-	54
140	12	12	14	14	-	52
141	12	14	14	14	-	54
142	7	7	7	7	7	35
143	7	7	7	7	9	37
144	7	7	7	7	12	40
145	7	7	7	7	14	42
146	7	7	7	7	18	46
147	7	7	7	7	22	50
148	7	7	7	7	24	52
149	7	7	7	9	9	39
150	7	7	7	9	12	42
151	7	7	7	9	14	44
152	7	7	7	9	18	48
153	7	7	7	9	22	52
154	7	7	7	9	24	54
155	7	7	7	12	12	45
156	7	7	7	12	14	47
157	7	7	7	12	18	51
158	7	7	7	14	14	49
159	7	7	7	14	18	53
160	7	7	9	9	9	41
161	7	7	9	9	12	44
162	7	7	9	9	14	46
163	7	7	9	9	18	50
164	7	7	9	9	22	54
165	7	7	9	12	12	47
166	7	7	9	12	14	49
167	7	7	9	12	18	53
168	7	7	9	14	14	51
169	7	7	12	12	12	50
170	7	7	12	12	14	52
171	7	7	12	14	14	54
172	7	9	9	9	9	43
173	7	9	9	9	12	46
174	7	9	9	9	14	48
175	7	9	9	9	18	52
176	7	9	9	12	12	49
177	7	9	9	12	14	51
178	7	9	9	14	14	53
179	7	9	12	12	12	52
180	7	9	12	12	14	54
181	9	9	9	9	9	45
182	9	9	9	9	12	48
183	9	9	9	9	14	50
184	9	9	9	9	18	54
185	9	9	9	12	12	51
186	9	9	9	12	14	53
187	9	9	12	12	12	54

NOTE: Up to 2 units of Medium static pressure duct are connectable to the combination.

2 - 5 Room Multi System Unit Reference Guide

UNIT NO.	BULKHEAD	MINI DUCT	MID STATIC SLIMLINE	WALL MOUNTED	CASSETTE	CEILING CONSOLE
7				ASTH07KMCD		
9	ARTH09KLLAP	ARTH09KSLAP		ASTH09KMCD	AUTH09KVL-GR	
12	ARTH12KLLAP	ARTH12KSLAP		ASTH12KMCD	AUTH12KVL-GR	
14				ASTH14KMCD		
18	ARTH18KLLAP	ARTH18KSLAP	ARTH18KMTAP	ASTH18KMTD	AUTH18KVL-GR	ABTH18KRTA
22				ASTH22KMTD		
24			ARTH24KMTAP	ASTH24KMTE		

NOTE: The connection charts reference possible combinations as per capacity class, please refer to technical manual for actual indoor capacities.

Connection Charts

AOTH45KBTA5 (2 - 5 ROOMS)

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
1	12	24	-	-	-	36
2	14	22	-	-	-	36
3	14	24	-	-	-	38
4	18	18	-	-	-	36
5	18	22	-	-	-	40
6	18	24	-	-	-	42
7	22	22	-	-	-	44
8	22	24	-	-	-	46
9	24	24	-	-	-	48
10	7	7	22	-	-	36
11	7	7	24	-	-	38
12	7	9	18	-	-	34
13	7	9	22	-	-	38
14	7	9	24	-	-	40
15	7	12	18	-	-	37
16	7	12	22	-	-	41
17	7	12	24	-	-	43
18	7	14	14	-	-	35
19	7	14	18	-	-	39
20	7	14	22	-	-	43
21	7	14	24	-	-	45
22	7	18	18	-	-	43
23	7	18	22	-	-	47
24	7	18	24	-	-	49
25	7	22	22	-	-	51
26	7	22	24	-	-	53
27	7	24	24	-	-	55
28	9	9	18	-	-	36
29	9	9	22	-	-	40
30	9	9	24	-	-	42
31	9	12	14	-	-	35
32	9	12	18	-	-	39
33	9	12	22	-	-	43
34	9	12	24	-	-	45
35	9	14	14	-	-	37
36	9	14	18	-	-	41
37	9	14	22	-	-	45
38	9	14	24	-	-	47
39	9	18	18	-	-	45
40	9	18	22	-	-	49
41	9	18	24	-	-	51
42	9	22	22	-	-	53
43	9	22	24	-	-	55
44	9	24	24	-	-	57
45	12	12	12	-	-	36
46	12	12	14	-	-	38
47	12	12	18	-	-	42
48	12	12	22	-	-	46
49	12	12	24	-	-	48
50	12	14	14	-	-	40
51	12	14	18	-	-	44
52	12	14	22	-	-	48
53	12	14	24	-	-	50
54	12	18	18	-	-	48
55	12	18	22	-	-	52
56	12	18	24	-	-	54
57	12	22	22	-	-	56
58	12	22	24	-	-	58
59	12	24	24	-	-	60
60	14	14	14	-	-	42
61	14	14	18	-	-	46
62	14	14	22	-	-	50
63	14	14	24	-	-	52
64	14	18	18	-	-	50
65	14	18	22	-	-	54

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
66	14	18	24	-	-	56
67	14	22	22	-	-	58
68	14	22	24	-	-	60
69	14	24	24	-	-	62
70	18	18	18	-	-	54
71	18	18	22	-	-	58
72	18	18	24	-	-	60
73	7	7	7	14	-	35
74	7	7	7	18	-	39
75	7	7	7	22	-	43
76	7	7	7	24	-	45
77	7	7	9	12	-	35
78	7	7	9	14	-	37
79	7	7	9	18	-	41
80	7	7	9	22	-	45
81	7	7	9	24	-	47
82	7	7	12	12	-	38
83	7	7	12	14	-	40
84	7	7	12	18	-	44
85	7	7	12	22	-	48
86	7	7	12	24	-	50
87	7	7	14	14	-	42
88	7	7	14	18	-	46
89	7	7	14	22	-	50
90	7	7	14	24	-	52
91	7	7	18	18	-	50
92	7	7	18	22	-	54
93	7	7	18	24	-	56
94	7	7	22	22	-	58
95	7	7	22	24	-	60
96	7	7	24	24	-	62
97	7	9	9	9	-	34
98	7	9	9	12	-	37
99	7	9	9	14	-	39
100	7	9	9	18	-	43
101	7	9	9	22	-	47
102	7	9	9	24	-	49
103	7	9	12	12	-	40
104	7	9	12	14	-	42
105	7	9	12	18	-	46
106	7	9	12	22	-	50
107	7	9	12	24	-	52
108	7	9	14	14	-	44
109	7	9	14	18	-	48
110	7	9	14	22	-	52
111	7	9	14	24	-	54
112	7	9	18	18	-	52
113	7	9	18	22	-	56
114	7	9	18	24	-	58
115	7	12	12	12	-	43
116	7	12	12	14	-	45
117	7	12	12	18	-	49
118	7	12	12	22	-	53
119	7	12	12	24	-	55
120	7	12	14	14	-	47
121	7	12	14	18	-	51
122	7	12	14	22	-	55
123	7	12	14	24	-	57
124	7	12	18	18	-	55
125	7	12	18	22	-	59
126	7	12	18	24	-	61
127	7	14	14	14	-	49
128	7	14	14	18	-	53
129	7	14	14	22	-	57
130	7	14	14	24	-	59

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
131	7	14	18	18	-	57
132	7	18	18	18	-	61
133	9	9	9	9	-	36
134	9	9	9	12	-	39
135	9	9	9	14	-	41
136	9	9	9	18	-	45
137	9	9	9	22	-	49
138	9	9	9	24	-	51
139	9	9	12	12	-	42
140	9	9	12	14	-	44
141	9	9	12	18	-	48
142	9	9	12	22	-	52
143	9	9	12	24	-	54
144	9	9	14	14	-	46
145	9	9	14	18	-	50
146	9	9	14	22	-	54
147	9	9	14	24	-	56
148	9	9	18	18	-	54
149	9	9	18	22	-	58
150	9	9	18	24	-	60
151	9	12	12	12	-	45
152	9	12	12	14	-	47
153	9	12	12	18	-	51
154	9	12	12	22	-	55
155	9	12	12	24	-	57
156	9	12	14	14	-	49
157	9	12	14	18	-	53
158	9	12	14	22	-	57
159	9	12	14	24	-	59
160	9	12	18	18	-	57
161	9	14	14	14	-	51
162	9	14	14	18	-	55
163	9	14	14	22	-	59
164	9	14	14	24	-	61
165	9	14	18	18	-	59
166	12	12	12	12	-	48
167	12	12	12	14	-	50
168	12	12	12	18	-	54
169	12	12	12	22	-	58
170	12	12	12	24	-	60
171	12	12	14	14	-	52
172	12	12	14	18	-	56
173	12	12	14	22	-	60
174	12	12	14	24	-	62
175	12	12	18	18	-	60
176	12	14	14	14	-	54
177	12	14	14	18	-	58
178	12	14	18	18	-	62
179	7	7	7	7	7	35
180	7	7	7	7	9	37
181	7	7	7	7	12	40
182	7	7	7	7	14	42
183	7	7	7	7	18	46
184	7	7	7	7	22	50
185	7	7	7	7	24	52
186	7	7	7	9	9	39
187	7	7	7	9	12	42
188	7	7	7	9	14	44
189	7	7	7	9	18	48
190	7	7	7	9	22	52
191	7	7	7	9	24	54
192	7	7	7	12	12	45
193	7	7	7	12	14	47
194	7	7	7	12	18	51
195	7	7	7	12	22	55

2 - 5 Room Multi System Unit Reference Guide

UNIT NO.	BULKHEAD	MINI DUCT	MID STATIC SLIMLINE	WALL MOUNTED	CASSETTE	CEILING CONSOLE
7				ASTH07KMCD		
9	ARTH09KLLAP	ARTH09KSLAP		ASTH09KMCD	AUTH09KVL-GR	
12	ARTH12KLLAP	ARTH12KSLAP		ASTH12KMCD	AUTH12KVL-GR	
14				ASTH14KMCD		
18	ARTH18KLLAP	ARTH18KSLAP	ARTH18KMTAP	ASTH18KMTD	AUTH18KVL-GR	ABTH18KRTA
22				ASTH22KMTD		
24			ARTH24KMTAP	ASTH24KMTE		

NOTE: The connection charts reference possible combinations as per capacity class, please refer to technical manual for actual indoor capacities.

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
196	7	7	7	12	24	57
197	7	7	7	14	14	49
198	7	7	7	14	18	53
199	7	7	7	14	22	57
200	7	7	7	14	24	59
201	7	7	7	18	18	57
202	7	7	9	9	9	41
203	7	7	9	9	12	44
204	7	7	9	9	14	46
205	7	7	9	9	18	50
206	7	7	9	9	22	54
207	7	7	9	9	24	56
208	7	7	9	12	12	47
209	7	7	9	12	14	49
210	7	7	9	12	18	53
211	7	7	9	12	22	57
212	7	7	9	12	24	59
213	7	7	9	14	14	51
214	7	7	9	14	18	55
215	7	7	9	14	22	59
216	7	7	9	14	24	61
217	7	7	9	18	18	59
218	7	7	12	12	12	50
219	7	7	12	12	14	52
220	7	7	12	12	18	56
221	7	7	12	12	22	60
222	7	7	12	12	24	62
223	7	7	12	14	14	54
224	7	7	12	14	18	58
225	7	7	12	18	18	62
226	7	7	14	14	14	56
227	7	7	14	14	18	60
228	7	9	9	9	9	43
229	7	9	9	9	12	46
230	7	9	9	9	14	48
231	7	9	9	9	18	52
232	7	9	9	9	22	56
233	7	9	9	9	24	58
234	7	9	9	12	12	49
235	7	9	9	12	14	51
236	7	9	9	12	18	55
237	7	9	9	12	22	59
238	7	9	9	12	24	61
239	7	9	9	14	14	53
240	7	9	9	14	18	57
241*	7	9	9	18	18	61
242	7	9	12	12	12	52
243	7	9	12	12	14	54
244	7	9	12	12	18	58
245	7	9	12	14	14	56
246	7	9	12	14	18	60
247	7	9	14	14	14	58
248	7	9	14	14	18	62
249	7	12	12	12	12	55
250	7	12	12	12	14	57
251	7	12	12	12	18	61
252	7	12	12	14	14	59
253	7	12	14	14	14	61
254	9	9	9	9	9	45
255	9	9	9	9	12	48
256	9	9	9	9	14	50
257	9	9	9	9	18	54
258	9	9	9	9	22	58
259	9	9	9	9	24	60
260	9	9	9	12	12	51

COMBINATION NO.	UNIT 1	UNIT 2	UNIT 3	UNIT 4	UNIT 5	TOTAL
261	9	9	9	12	14	53
262	9	9	9	12	18	57
263	9	9	9	14	14	55
264	9	9	9	14	18	59
265	9	9	12	12	12	54
266	9	9	12	12	14	56
267	9	9	12	12	18	60
268	9	9	12	14	14	58
269	9	9	12	14	18	62
270	9	9	14	14	14	60
271	9	12	12	12	12	57
272	9	12	12	12	14	59
273	9	12	12	14	14	61
274	12	12	12	12	12	60
275	12	12	12	12	14	62

NOTE: Up to 2 units of Medium static pressure duct are connectable to the combination. However, in the combination marked with *, only 1 unit of Medium static pressure duct is connectable.

2 - 5 Room Multi System Unit Reference Guide

UNIT NO.	BULKHEAD	MINI DUCT	MID STATIC SLIMLINE	WALL MOUNTED	CASSETTE	CEILING CONSOLE
7				ASTH07KMCD		
9	ARTH09KLLAP	ARTH09KSLAP		ASTH09KMCD	AUTH09KVL-GR	
12	ARTH12KLLAP	ARTH12KSLAP		ASTH12KMCD	AUTH12KVL-GR	
14				ASTH14KMCD		
18	ARTH18KLLAP	ARTH18KSLAP	ARTH18KMTAP	ASTH18KMTD	AUTH18KVL-GR	ABTH18KRTA
22				ASTH22KMTD		
24			ARTH24KMTAP	ASTH24KMTE		

NOTE: The connection charts reference possible combinations as per capacity class, please refer to technical manual for actual indoor capacities.

NEW ZEALAND'S FAVOURITE AIR®

| FUJITSU

FUJITSU GENERAL AUSTRALIA
A SUBSIDIARY OF FUJITSU GENERAL LIMITED

fujitsugeneral.com.au
1300 882 201
contact@fujitsugeneral.com.au

Fujitsu General accepts no liability for incorrect data.
Please ensure you have confirmed installation
requirements and pipe sizes prior to install.

FGAMULTI08/25

AIRSTAGE