

# Rinnai



## Rinnai Cooling

Portable Air Conditioning Range



Wireless  
Control



Temperature  
Control



2 Year  
Warranty



Timer for  
Convenience



Multiple  
Speed Fan



[rinnai.com.au](http://rinnai.com.au)

## Rinnai Portable Cooling

Australia's ever changing living spaces require flexible, efficient cooling solutions tailored to unique comfort needs. Rinnai Portable Air Conditioners have all the practical functions, including an intelligent sleep mode, inbuilt timer and self evaporative system - meaning comfort is maintained while keeping the bills down. The RPC35PDRWF model is unique in its category with reverse cycle heating and cooling.

## Features and Benefits

- Sleep mode
- Adjustable temp control
- Inbuilt timer
- Water alarm
- Wi-Fi and remote control
- No need to empty water\*
- Washable filter
- 2 year warranty
- Ventilation kit included

## Specifications

|                               |                |  |  |  |  |
|-------------------------------|----------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
|                               |                | RPC26MCWF                                                                         | RPC34MCWF                                                                         | RPC41MCWF                                                                         | RPC35PDRWF                                                                         |
| Function                      |                | Cooling Only                                                                      |                                                                                   |                                                                                   | Heating and Cooling                                                                |
| Control Method                |                | Remote and Wi-Fi via App                                                          |                                                                                   |                                                                                   |                                                                                    |
| Rated Voltage/Frequency       |                | 220-240 Volts / 50Hz                                                              |                                                                                   |                                                                                   |                                                                                    |
| Rated Cooling Input Power     | W              | 1000                                                                              | 1280                                                                              | 1640                                                                              | 1350                                                                               |
| Cooling Capacity              | kW             | 2.6                                                                               | 3.4                                                                               | 4.1                                                                               | 3.5                                                                                |
| EER                           | W/W            | 2.6                                                                               | 2.6                                                                               | 2.5                                                                               | 2.59                                                                               |
| Rated Heating Input Power     | W              | -                                                                                 | -                                                                                 | -                                                                                 | 1045                                                                               |
| Heating Capacity              | kW             | -                                                                                 | -                                                                                 | -                                                                                 | 3.00                                                                               |
| COP                           | W/W            | -                                                                                 | -                                                                                 | -                                                                                 | 2.87                                                                               |
| Refrigerant Type              |                | R290                                                                              | R290                                                                              | R290                                                                              | R290                                                                               |
| Refrigerant Volume            | g              | 160                                                                               | 210                                                                               | 240                                                                               | 220                                                                                |
| Sound Power Level             | dB(A)          | 64                                                                                | 65                                                                                | 64                                                                                | 62.7                                                                               |
| Product Dimension (H x W x D) | mm             | 710 x 415 x 345                                                                   | 710 x 476 x 385                                                                   | 802 x 493 x 415                                                                   | 765 x 467 x 397                                                                    |
| Product Weight                | kg             | 28.5                                                                              | 33                                                                                | 36.5                                                                              | 33.2                                                                               |
| Ideal Application Area**      | m <sup>2</sup> | Min 11-20                                                                         | Min 12-24                                                                         | Min 13-30                                                                         | Min 12-24                                                                          |

## How do Rinnai Portable Air Conditioners work?

- Air from the room is drawn into the air conditioner, cooled by refrigeration and blown out the front grill.
- Hot air is blown outside through the exhaust hose, using the window kit supplied with the air conditioner.
- Hot air must be exhausted outside the room being cooled, or you will not cool the room.

## Which model is right for me?

It's important to choose model is right for you! The room conditions should be considered when selecting your Rinnai Portable Cooler. For best performance, the cooler should be in a well insulated and sealed ground floor room with external walls facing east and/or south.

For further information call **1300 555 545** or visit **rinnai.com.au**

\* Climate conditions where high humidity is present may require drainage.

\*\* Product must be operated in accordance with minimum room size requirements as detailed in the owners manual.